

Water and Water Mist

Our water and water mist extinguishers bring effective and affordable protection for common combustible fires. Both the water and water mist units have Schrader Valves incorporated into the valve assemblies for convenient recharge with a standard bicycle pump.

The water mist unit uses deionized water and uses a particular spray nozzle. These aspects make it safe for use on energized electrical equipment. Water mist is designed to be the extinguisher of choice for libraries and hospitals.

Water Extinguisher =

- **Class A** - Ordinary combustibles: wood, paper, rubber, fabrics, and many plastics

Water Mist Extinguisher =

- **Class A** - Ordinary combustibles: wood, paper, rubber, fabrics, and many plastics
- **Class C** - Fires involving live electrical equipment

Specifications:

- UL & ULC Listed
- Aluminum valve
- Wall mount included
- Rechargeable
- USA Made



Part #	EXT25GAL	EXT25GALM
Mfg. Part #	50000	51000
Cylinder/Valve Material	Stainless Steel/Plated Brass	Stainless Steel/Plated Brass
Agent Capacity	2.5 gallons	2.5 gallons
UL/ULC Rating	2-A	2-A:C
Temperature Range	40° to 120°F	40° to 120°F
Discharge Time	50 sec	73 sec
Discharge Range	45 to 55 ft.	5 to 10 ft.
Operating Pressure	100 psi	100 psi
Mounting Type	Wall	Wall
USCG Approval	Type A Size II	N/A
Ship Weight	Empty: 8.3 lb.	Full: 30.25 lb.
Unit Height	24.5 in	28 in
Unit Width (Incl. Hose)	9 in	14 in
Unit Diameter	7 in	7 in